

Honeywell Specialty Chemicals Seelze GmbH
 Wunstorferstrasse 40
 Seelze, 30926
 Telefon: +49 5137 999-0
lab.honeywell.com

Brand: Honeywell Riedel-de Haën
 Product: 34967
 Lot No: N244B
 Production date: 01.Sep.2023
 Expiry Date: 21.Aug.2025

Acetonitrile LC-MS CHROMASOLV

Parameter	Specification	Units	Result	Units
assay (GC)	min. 99.9	%	>99.99	%
propionitrile (GC)	max. 0.2	%	<0.2	%
non-volatile matter	max. 0.0002	%	<0.0002	%
water (Karl Fischer)	max. 0.01	%	0.001	%
free acid (as CH ₃ COOH)	max. 0.001	%	0.0009	%
free alkali (as NH ₃)	max. 0.0001	%	<0.0001	%
silver (Ag)	max. 0.1	ppm	<0.1	ppm
aluminium (Al)	max. 0.5	ppm	<0.5	ppm
barium (Ba)	max. 0.1	ppm	<0.1	ppm
bismuth (Bi)	max. 0.1	ppm	<0.1	ppm
calcium (Ca)	max. 0.05	ppm	<0.05	ppm
cadmium (Cd)	max. 0.05	ppm	<0.05	ppm
cobalt (Co)	max. 0.02	ppm	<0.02	ppm
chromium (Cr)	max. 0.02	ppm	<0.02	ppm
copper (Cu)	max. 0.02	ppm	<0.02	ppm
iron (Fe)	max. 0.02	ppm	<0.02	ppm
potassium (K)	max. 0.05	ppm	<0.05	ppm
lithium (Li)	max. 0.1	ppm	<0.1	ppm
magnesium (Mg)	max. 0.1	ppm	<0.1	ppm
manganese (Mn)	max. 0.02	ppm	<0.02	ppm
molybdenum (Mo)	max. 0.1	ppm	<0.1	ppm
sodium (Na)	max. 0.05	ppm	<0.05	ppm
nickel (Ni)	max. 0.02	ppm	<0.02	ppm
lead (Pb)	max. 0.02	ppm	<0.02	ppm
tin (Sn)	max. 0.1	ppm	<0.1	ppm
strontium (Sr)	max. 0.1	ppm	<0.1	ppm

Acetonitrile LC-MS CHROMASOLV

Parameter	Specification	Units	Result	Units
zinc (Zn)	max. 0.1	ppm	<0.1	ppm
HPLC-gradient at 210 nm	max. 1	mAU	<1	mAU
HPLC-gradient at 254 nm	max. 0.2	mAU	<0.2	mAU
baseline drift at 210 nm	max. 12	mAU	<12	mAU
suitability for the LC-MS	complying		complying	
fluorescence (chinin) at 254 nm	max. 0.5	ppb	<0.5	ppb
fluorescence (chinin) at 365 nm	max. 0.5	ppb	<0.5	ppb
absorbance at 195 nm	max. 0.097		<0.097	
absorbance at 200 nm	max. 0.022		<0.022	
absorbance at 230 nm	max. 0.0044		<0.0044	



filtered via 0,2µm pore size filter

QC Release Date: 12.Sep.2023

The minimum shelf life is based on the current knowledge and holds only for proper storage conditions in the originally closed flasks/ packages.

We herewith confirm that the delivery is effected according to the technical delivery conditions agreed.

Particular properties of the products or the suitability for a particular area of application are not assured.

We guarantee a proper quality within our General Conditions of Sales.

Honeywell

Quality Management

This document was produced electronically and is valid without a signature